


SUB-ROLLUP GREY BACK / 1066-16

Komposition Composition	100% Polyester
Gewicht Weight	305 g/m ² (±5%)
Dicke Thickness	0,36 mm (±5%)
Verarbeitung Processing	kalt schneiden cold cut
Breite Width	155 cm, 260cm, 310 cm
Weißgrad Whiteness	>140
Tintentyp / Druckseite Ink Type / Print Side	Sublimation Direct / inside, UV-Curable* / inside Latex / inside, Sublimation Transfer / inside
Anwendung Use	Frontlit, Roll Up, Werbebanner, Rollo Fensterverdunklung, Interior Design. Frontlit, Roll Up, Advertising banners, Roller blinds, Interior design.
Schwerentflammbarkeit Flame retardancy	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B / M1***



* UV-Tinten können das Schüsseln (Curlen) des Textils verursachen, vor dem eigentlichen Druckauftrag sollten immer erst Testdrucke durchgeführt werden.

** Bei Verwendung von Latex Tinten bitte vorher testen ob das Hinterleuchtungsergebnis ausreicht.

*** Bald erhältlich.

Alle obigen Informationen und Spezifikationen sind als Leitfaden gedacht. Wir behalten uns das Recht vor, Änderungen, die im Rahmen einer kontinuierlichen Produktverbesserung stattfinden, ohne spezielle schriftliche Mitteilung vorzunehmen.

* UV-inks could cause curling and test prints for suitability must always be carried out before actual printing job.

** Latex Ink backlight results are limited.

*** Available soon.

All above information and specifications are intended as a guide only. We reserve the right to change, alter or modify these information and specifications without prior written notice from time to time subject to a programme of continuous product improvement.