


**MICRO-SATIN UNIVERSAL / 1007-12**

Komposition Composition	100% Polyester
Gewicht Weight	165 g/m <sup>2</sup> (±5%)
Dicke Thickness	0,21 mm (±5%)
Verarbeitung Processing	kalt schneiden cold cut
Breite Width	155 cm, 255 cm, 310 cm
Weißgrad Whiteness	>120
Tintentyp / Druckseite Ink Type / Print Side	Latex / inside, UV-Curable* / inside Sublimation Direct / outside, Sublimation Transfer / outside
Anwendung Use	Leuchtkästen, Display Rahmensysteme, Werbebanner. Light boxes, display frame systems, advertising banners.
Schwerentflammbarkeit Flame retardancy	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B / M1***



\* UV-Tinten können das Schüsseln (Curlen) des Textils verursachen, vor dem eigentlichen Druckauftrag sollten immer erst Testdrucke durchgeführt werden.

\*\* Bei Verwendung von Latex Tinten bitte vorher testen ob das Hinterleuchtungsergebnis ausreicht.

\*\*\* Bald erhältlich.

Alle obigen Informationen und Spezifikationen sind als Leitfaden gedacht. Wir behalten uns das Recht vor, Änderungen, die im Rahmen einer kontinuierlichen Produktverbesserung stattfinden, ohne spezielle schriftliche Mitteilung vorzunehmen.

\* UV-inks could cause curling and test prints for suitability must always be carried out before actual printing job.

\*\* Latex Ink backlight results are limited.

\*\*\* Available soon.

All above information and specifications are intended as a guide only. We reserve the right to change, alter or modify these information and specifications without prior written notice from time to time subject to a programme of continuous product improvement.

